

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare V-11 VT

Version		Revision Date:	Date of last issue: 16.06.2022
2.3	DE / EN	05.10.2023	Date of first issue: 15.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Yachtcare V-11 VT
Product code : 153.404

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Body filler/stopper
Recommended restrictions on use : Industrial use, professional use, public use

1.3 Details of the supplier of the safety data sheet

Company : Vosschemie GmbH
Esinger Steinweg 50
25436 Uetersen
Germany
info@vosschemie.de
Telephone : 04122 717 0
Telefax : 04122 717158
Responsible Department : Laboratory
04122 717 0
sds@vosschemie.de

1.4 Emergency telephone

Telephone : Giftinformationszentrum (GIZ)-Nord,
Göttingen, Deutschland
0551 19240

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare V-11 VT

Version
2.3

DE / EN

Revision Date:
05.10.2023

Date of last issue: 16.06.2022
Date of first issue: 15.06.2022

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3

H226: Flammable liquid and vapor.

Skin irritation, Category 2

H315: Causes skin irritation.

Eye irritation, Category 2

H319: Causes serious eye irritation.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal Word

: Warning

Hazard Statements

: H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

: P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare V-11 VT

Version
2.3

DE / EN

Revision Date:
05.10.2023

Date of last issue: 16.06.2022
Date of first issue: 15.06.2022

Additional Labeling

EUH208 Contains Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture
contains
Resin

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
vinyltoluene	25013-15-4 246-562-2 01-2119622074-50, 01-2120106403-73	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 M-Factor (Acute aquatic toxicity): 1	>= 10 - < 20
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-	Not Assigned 911-490-9 01-2119979579-10	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1B; H317 Aquatic Chronic 3; H412 Acute toxicity esti-	>= 0,25 - < 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare V-11 VT

Version
2.3

DE / EN

Revision Date:
05.10.2023

Date of last issue: 16.06.2022
Date of first issue: 15.06.2022

		mate	
		Acute oral toxicity: 619 mg/kg	
Substances with a workplace exposure limit :			
Talc	14807-96-6 238-877-9		>= 30 - < 50

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
Move out of dangerous area.
Take off contaminated clothing and shoes immediately.
Do not leave the victim unattended.
Symptoms of poisoning may appear several hours later.
Show this material safety data sheet to the doctor in attendance.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Call a physician if irritation develops or persists.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Keep eye wide open while rinsing.
If easy to do, remove contact lens, if worn.
Consult a physician.
- If swallowed : Do NOT induce vomiting.
Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.
Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
Keep under medical supervision for at least 48 hours.

Yachtcare V-11 VT

Version	Revision Date:	Date of last issue: 16.06.2022
2.3 DE / EN	05.10.2023	Date of first issue: 15.06.2022

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Carbon dioxide (CO₂)
Dry powder
Water spray jet
Alcohol-resistant foam

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

Hazardous combustion products : Hazardous decomposition products due to incomplete combustion
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Further information : Use water spray to cool unopened containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Wear personal protective equipment.
Evacuate personnel to safe areas.
Ensure adequate ventilation, especially in confined areas.
Remove all sources of ignition.
Do not smoke.
Avoid contact with skin, eyes and clothing.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare V-11 VT

Version 2.3 DE / EN Revision Date: 05.10.2023 Date of last issue: 16.06.2022
Date of first issue: 15.06.2022

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
Do not flush with water.

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Keep container closed when not in use.
Provide sufficient air exchange and/or exhaust in work rooms.
Wear personal protective equipment.
Avoid contact with skin and eyes.
Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture.
Avoid inhalation of dust from sanding.

Advice on protection against fire and explosion : Vapors may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.

Further information on storage conditions : Keep away from heat and sources of ignition. Keep away from direct sunlight.

Advice on common storage : Incompatible with oxidizing agents.
Keep away from food and drink.

Storage class (TRGS 510) : 3

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Talc	14807-96-6	AGW (Inhalable)	10 mg/m ³	DE TRGS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE**Yachtcare V-11 VT**Version
2.3

DE / EN

Revision Date:
05.10.2023Date of last issue: 16.06.2022
Date of first issue: 15.06.2022

		fraction)		900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m ³	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		TWA (Respirable dust)	0,1 mg/m ³	2004/37/EC
	Further information: Carcinogens or mutagens			
Barium sulphate	7727-43-7	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m ³	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
vinyltoluene	25013-15-4	AGW	20 ppm 98 mg/m ³	DE TRGS 900
	Peak-limit category: 2;(I)			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
vinyltoluene	Workers	Inhalation	Long-term systemic effects	5,82 mg/m ³
	Workers	Dermal	Long-term systemic effects	1,65 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,595 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	0,595 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,03 mg/m ³
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-	Workers	Inhalation	Long-term systemic effects	9,8 mg/m ³
	Workers	Skin contact	Long-term systemic effects	1,4 mg/kg
	Consumers	Inhalation	Long-term systemic effects	2,9 mg/m ³
	Consumers	Skin contact,	Long-term systemic	0,83 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare V-11 VT

Version
2.3

DE / EN

Revision Date:
05.10.2023

Date of last issue: 16.06.2022
Date of first issue: 15.06.2022

		Oral	effects	
--	--	------	---------	--

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
vinyltoluene	Fresh water	0,000319 mg/l
	Sea water	0,000032 mg/l
	Fresh water sediment	0,032 mg/kg dry weight (d.w.)
	Sea sediment	0,0032 mg/kg dry weight (d.w.)
	Soil	0,00621 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	5,92 mg/l
	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-	Fresh water
	Sea water	0,005 mg/l
	Sewage treatment plant (STP)	10 mg/l
	Fresh water sediment	1,2 mg/kg
	Sea sediment	0,12 mg/kg
	Soil	0,21 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : Fluorinated rubber
Break through time : > 480 min
Glove thickness : \geq 0,4 mm
Directive : DIN EN 374
Protective index : Class 6

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : \geq 0,4 mm
Directive : DIN EN 374
Protective index : Class 6

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection Butyl gloves are not suitable. Avoid natural rubber gloves.

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare V-11 VT

Version		Revision Date:	Date of last issue: 16.06.2022
2.3	DE / EN	05.10.2023	Date of first issue: 15.06.2022

- or heat-resistant synthetic fibres.
Long sleeved clothing
- Respiratory protection : Apply technical measures to comply with the occupational exposure limits.
If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
Dry sanding, flame cutting and/or welding of the cured material will give rise to dust and/or hazardous fumes.
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).
- Filter type : Combined particulates and organic vapor type (A-P)
- Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.
Avoid contact with the skin and the eyes.
Use only with adequate ventilation.
-

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : paste
- Color : beige
- Odor : aromatic
- Melting point/freezing point : -76,8 °C
Literature value vinyltoluene
- Boiling point/boiling range : 168 °C
Literature value vinyltoluene
- Upper explosion limit / Upper flammability limit : 6,1 %(V)
Literature value vinyltoluene
- Lower explosion limit / Lower flammability limit : 1,9 %(V)
Literature value vinyltoluene
- Flash point : 53 °C
Literature value vinyltoluene
- Autoignition temperature : 575 °C
Literature value vinyltoluene
- Decomposition temperature : No data available
- pH : Not applicable substance/mixture is non-soluble (in water)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare V-11 VT

Version	Revision Date:	Date of last issue: 16.06.2022
2.3 DE / EN	05.10.2023	Date of first issue: 15.06.2022

Viscosity
Viscosity, dynamic : not determined

Viscosity, kinematic : not determined

Solubility(ies)
Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapor pressure : 2 hPa (20 °C)
Literature value vinyltoluene

Density : ca. 1,8 g/cm³ (20 °C)

Relative vapor density : No data available

9.2 Other information

Explosives : Not explosive
In use, may form flammable/explosive vapor-air mixture.

Flammability (liquids) : Flammable

Self-ignition : not auto-flammable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Avoid radical-forming starting agents, peroxides and reactive metals.
Polymerization can occur. Polymerization is a highly exothermic reaction and may generate sufficient heat to cause thermal decomposition and/or rupture containers.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.

10.5 Incompatible materials

Materials to avoid : Strong acids and oxidizing agents
polymerization initiators

Yachtcare V-11 VTVersion
2.3

DE / EN

Revision Date:
05.10.2023Date of last issue: 16.06.2022
Date of first issue: 15.06.2022

10.6 Hazardous decomposition productsBuild-up of dangerous/toxic fumes possible in cases of fire/high temperature.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Components:**vinyltoluene:**

Acute oral toxicity : LD50 Oral (Rat): 3.375 mg/kg

Acute inhalation toxicity : LC50: > 16,89 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rabbit): 4.585 mg/kg

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-:

Acute oral toxicity : LD50 Oral (Rat): 619 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402

Talc:

Acute oral toxicity : LD50 Oral (Rat): 5.000 mg/kg
Method: OECD Test Guideline 423

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare V-11 VT

Version
2.3

DE / EN

Revision Date:
05.10.2023

Date of last issue: 16.06.2022
Date of first issue: 15.06.2022

Skin corrosion/irritation

Causes skin irritation.

Components:

vinyltoluene:

Assessment : Irritating to skin.
Result : Skin irritation

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-:

Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

vinyltoluene:

Assessment : Irritating to eyes.
Result : Moderate eye irritation

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-:

Result : Irreversible effects on the eye

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-:

Test Type : Local lymph node assay (LLNA)
Species : Mouse
Assessment : The product is a skin sensitizer, sub-category 1B.
Method : OECD Test Guideline 429
Result : positive

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare V-11 VT

Version
2.3

DE / EN

Revision Date:
05.10.2023

Date of last issue: 16.06.2022
Date of first issue: 15.06.2022

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

vinyltoluene:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

vinyltoluene:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 5,2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 9,3 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 0,319 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): 0,25 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox- : 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare V-11 VT

Version	Revision Date:	Date of last issue:
2.3	05.10.2023	16.06.2022
DE / EN		Date of first issue: 15.06.2022

icity)

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-:

- Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 48 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50 (Bacteria): > 1.000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

12.2 Persistence and degradability

Components:

vinyltoluene:

- Biodegradability : Result: Not readily biodegradable.
Biodegradation: 36,7 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

12.3 Bioaccumulative potential

Components:

vinyltoluene:

- Bioaccumulation : Concentration: 86,7 mg/l
- Partition coefficient: n-octanol/water : log Pow: 3,44

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-:

- Partition coefficient: n-octanol/water : log Pow: 2,17 (20 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare V-11 VT

Version	Revision Date:	Date of last issue: 16.06.2022
2.3 DE / EN	05.10.2023	Date of first issue: 15.06.2022

Talc:

Partition coefficient: n-octanol/water : log Pow: -9,4 (25 °C)
pH: 7

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
Dispose of in accordance with local regulations.
Dispose of wastes in an approved waste disposal facility.
Send to a licensed waste management company.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Store containers and offer for recycling of material when in accordance with the local regulations.
Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:
07 02 08, other still bottoms and reaction residues

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare V-11 VT

Version
2.3

DE / EN

Revision Date:
05.10.2023

Date of last issue: 16.06.2022
Date of first issue: 15.06.2022

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1866
ADR : UN 1866
RID : UN 1866
IMDG : UN 1866
IATA : UN 1866

14.2 UN proper shipping name

ADN : RESIN SOLUTION
ADR : RESIN SOLUTION
RID : RESIN SOLUTION
IMDG : RESIN SOLUTION
IATA : Resin solution

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADN
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare V-11 VT

Version	Revision Date:	Date of last issue: 16.06.2022
2.3 DE / EN	05.10.2023	Date of first issue: 15.06.2022

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare V-11 VT

Version	Revision Date:	Date of last issue: 16.06.2022
2.3 DE / EN	05.10.2023	Date of first issue: 15.06.2022

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2004/42/EC
Volatile organic compounds (VOC) content: < 250 g/l
VOC content for the product in a ready to use condition.

15.2 Chemical Safety Assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapor.
H302 : Harmful if swallowed.
H304 : May be fatal if swallowed and enters airways.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H400 : Very toxic to aquatic life.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare V-11 VT

Version 2.3 DE / EN Revision Date: 05.10.2023 Date of last issue: 16.06.2022
Date of first issue: 15.06.2022

Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitization
2004/37/EC	:	Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
2004/37/EC / TWA	:	Long term exposure limit
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare V-11 VT

Version
2.3

DE / EN

Revision Date:
05.10.2023

Date of last issue: 16.06.2022
Date of first issue: 15.06.2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN