

GTI 30 Antifouling

Field of use & Properties

Very thin layered, extremely slick and smooth antifouling with PTFE-anti stick effect. Thanks to the PTFE-technology there are no big amounts of color layers produced over the years of usage. It is suitable for Motoryacht as well as Sailing yacht hulls and especially suitable for gliders and regatta boats. This antifouling can be used in all waters but is especially suited for inland waters like rivers and lakes. It can be applied to GFK, steel and wood, though not suitable for aluminum.

Preparation

The undergrowth has to be dry, clean and grease free. Non sticking old layers have to be removed completely. The undergrowth already has to be treated with a two component epoxy primer (e.g. SEATEC EPOTEC) or a PTFE thin layered antifouling. Check the compatibility of SEATEC GTI 30 with the old bottom paint. If in doubt, we recommend a sticking test. Sanding down for another coating is not necessary. The antifouling can be put on directly. SEATEC GTI 30 can only be covered with itself or other PTFE-antifouling.

The antifouling is ready to use but should be stirred thoroughly before use.

The best way to paint on the antifouling is to use a paint brush or roller. The temperature should be a minimum of +12°C. Please also pay attention to the temperature of the bottom.

For a reconstruction a minimum of 2 layers SEATEC GTI 30 are recommended. It can be necessary to add an additional layer at the waterline and stronger burdened areas. The antifouling is quick drying. 1 hour (at 20°C) should be waited before putting on the second coating.

Processing

Color: half mat, copper or graphite gray

(Please make note: the SEATEC GTI antifouling develops its real color tone after permanent water contact.)

Coating with: paint brush or roller

Coating area: approx. 11,5m² per liter

Paint over with itself: after about 1 hour

Put into water after last coating: Wait min. 6 hours – max. 6 months

Recommended coatings for reconstruction: 2 layers

Recommended coatings for repeated coating: 1 layer

Use biocides safely. Before usage read declaration and product information. Do not reuse empty containers.

Note

Protect the product from moisture, frost and strong heat. The waste disposal has to be done according to local regulations. You can find more information at your local waste disposal companies. Always read the instructions on the declaration before usage.

Version: January 2015

With this version, all previous version will be made invalid.