

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.11.2015

V - 1

Revision: 18.11.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
 - **Trade name:** YACHTCARE EPOXY LIGHTFILLER (Hardener) *NEW*
 - **1.2 Relevant identified uses of the substance or mixture and uses advised against** Not determined
 - **Application of the substance / the mixture**
Hardening agent/ Curing agent
Knife filler/ Surfacer
 - **1.3 Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
Vosschemie GmbH
Esinger Steinweg 50
D-25436 Uetersen
Phone: +49 (0)4122 717 0; Fax: +49 (0)4122 717158; info@vosschemie.de
 - **Further information obtainable from:**
Abteilung Labor / +49 (0)4122 717 0
s.schaller@vosschemie.de
 - **1.4 Emergency telephone number:**
Giftinformationszentrum (GIZ)-Nord, Goettingen, Deutschland
Phone: +49 (0)551 19240
-

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.

(Contd. on page 2)

-GB-

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.11.2015

V - 1

Revision: 18.11.2015

Trade name: YACHTCARE EPOXY LIGHTFILLER (Hardener) *NEW*

(Contd. of page 1)



GHS07

Acute Tox. 4 H302 Harmful if swallowed.
Acute Tox. 4 H332 Harmful if inhaled.
Skin Sens. 1 H317 May cause an allergic skin reaction.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS05 GHS07

· **Signal word** Danger

· **Hazard-determining components of labelling:**

3-aminomethyl-3,5,5-trimethylcyclohexylamine
Benzyl alcohol
Fatty acids, C18-unsatd., trimers, compds. with oleyamine
N-(3-(trimethoxysilyl)propyl)ethylenediamine
Fatty acids, tall-oil, compds. with oleylamine

· **Hazard statements**

H302+H332 Harmful if swallowed or if inhaled.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.
· **vPvB:** Not applicable.

GB

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.11.2015

V - 1

Revision: 18.11.2015

Trade name: YACHTCARE EPOXY LIGHTFILLER (Hardener) *NEW*

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 100-51-6 EINECS: 202-859-9	Benzyl alcohol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332	10-<25%
CAS: 2855-13-2 EINECS: 220-666-8	3-aminomethyl-3,5,5-trimethylcyclohexylamine ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	10-<25%
CAS: 69-72-7 EINECS: 200-712-3 Reg.nr.: 01-2119486984-17	Salicylic acid ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302	1.0-<3.0%
CAS: 147900-93-4 EC number: 604-612-4 Reg.nr.: 01-2119971821-33	Fatty acids, C18-unsatd., trimers, compds. with oleyamine ⚠ STOT RE 2, H373; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H302; Skin Sens. 1B, H317	0.1-<0.5%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	0.1-<0.5%
CAS: 85711-55-3 EINECS: 288-315-1 Reg.nr.: 01-2119974148-28	Fatty acids, tall-oil, compds. with oleylamine ⚠ STOT RE 2, H373; ⚠ Eye Dam. 1, H318; ⚠ Skin Sens. 1A, H317	0.1-<0.5%
CAS: 1760-24-3 EINECS: 217-164-6	N-(3-(trimethoxysilyl)propyl)ethylenediamine ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	0.1-<0.5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Immediately remove any clothing soiled by the product.

· **After inhalation:**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

· **After eye contact:**

Rinse opened eye for several minutes under running water. Then consult a doctor.

Call a doctor immediately.

· **After swallowing:**

Do not induce vomiting; call for medical help immediately.

Rinse out mouth and then drink plenty of water.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.11.2015

V - 1

Revision: 18.11.2015

Trade name: YACHTCARE EPOXY LIGHTFILLER (Hardener) *NEW*

(Contd. of page 3)

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Carbon monoxide (CO)
Nitrogen oxides (NO_x)
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Avoid contact with the eyes and skin.
Ensure adequate ventilation
Do not inhale gases / fumes / aerosols.
Keep away from ignition sources.
- **6.2 Environmental precautions:**
Do not allow to penetrate the ground/soil.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Collect with an inert, non-combustible, absorbent material (i.e. sand, diatomaceous earth, acid binder, universal binder).
Dispose of the material collected according to regulations.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep receptacles tightly sealed.
Open and handle receptacle with care.
Ensure good ventilation/exhaustion at the workplace.
Avoid contact with the eyes and skin.
Prevent formation of aerosols.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.11.2015

V - 1

Revision: 18.11.2015

Trade name: YACHTCARE EPOXY LIGHTFILLER (Hardener) *NEW*

(Contd. of page 4)

- Do not inhale gases / fumes / aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
- **Information about storage in one common storage facility:**
Keep away from foodstuffs, beverages and feed.
Do not store together with oxidising and acidic materials.
Do not store together with alkalis (caustic solutions).
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Store receptacle in a well ventilated area.
Protect from humidity and water.
Protect from frost.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

69-72-7 Salicylic acid

Oral	Acute/short-term exposure - systemic effects	4 mg/kg bw/day (general population)
	Long-term exposure - systemic effects	1 mg/kg bw/day (general population)
Dermal	Long-term exposure - systemic effects	2 mg/kg bw/day (worker)
	Inhalative	Long-term exposure - systemic effects
	Long-term exposure - local effects	0.2 mg/m ³ (general population)

64742-95-6 Hydrocarbons, C9, aromatics

Oral	Long-term exposure - systemic effects	11 mg/kg bw/day (general population)
Dermal	Long-term exposure - systemic effects	11 mg/kg bw/day (general population)
		25 mg/kg bw/day (worker)
Inhalative	Long-term exposure - systemic effects	32 mg/m ³ (general population)
		150 mg/m ³ (worker)

· **PNECs**

69-72-7 Salicylic acid

PNEC aqua	0.2 mg/l (freshwater)
	0.02 mg/l (marine water)
PNEC sediment	1.42 mg/kg (freshwater)
	0.142 mg/kg (marine water)

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.11.2015

V - 1

Revision: 18.11.2015

Trade name: YACHTCARE EPOXY LIGHTFILLER (Hardener) *NEW*

(Contd. of page 5)

PNEC STP	162 mg/l (-)
----------	--------------

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Do not eat, drink, smoke or sniff while working.

Store protective clothing separately.

Immediately remove all soiled and contaminated clothing

Take off contaminated clothing.

Wash hands before breaks and at the end of work.

Use skin protection cream for skin protection.

Avoid contact with the eyes and skin.

After contact with skin, wash immediately with plenty of soap and water.

· **Respiratory protection:**

Ensure good ventilation/exhaustion at the workplace.

Adhere to the workplace limit values and / or other threshold values.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check the permeability prior to each renewed use of the glove.

Preventive skin protection by use of skin-protecting agents is recommended.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Fluorocarbon rubber (Viton)

Recommended thickness of the material: ≥ 0.7 mm

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For special applications, it is recommended to verify the chemical resistance of the above stated protective gloves with the manufacturer.

· **Eye protection:**



Tightly sealed goggles

Face protection

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.11.2015

V - 1

Revision: 18.11.2015

Trade name: YACHTCARE EPOXY LIGHTFILLER (Hardener) *NEW*

(Contd. of page 6)

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Pasty
Colour: Yellow
Odour: Characteristic

· **Change in condition**

Boiling point/Boiling range: Undetermined.

· **Flash point:** > 100 °C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Density at 20 °C:** 0.95 g/ml

· **Solubility in / Miscibility with water:**

Insoluble.

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No decomposition if used and stored according to specifications.

· **10.2 Chemical stability** No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions** Reacts with acids, alkalis and oxidising agents.

· **10.4 Conditions to avoid**

Protect from heat.

Avoid naked flames, sparks, other ignition sources and sunlight.

Protect from frost.

· **10.5 Incompatible materials:** Reacts with acids, alkalis and oxidising agents.

· **10.6 Hazardous decomposition products:**

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

SECTION 11: Toxicological information

· **11.1 Information on toxicological effects**

· **Acute toxicity**

Harmful if swallowed or if inhaled.

· **LD/LC50 values relevant for classification:**

100-51-6 Benzyl alcohol

Oral	LD 50	1230 mg/kg (rat)
------	-------	------------------

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.11.2015

V - 1

Revision: 18.11.2015

Trade name: YACHTCARE EPOXY LIGHTFILLER (Hardener) *NEW*

(Contd. of page 7)

Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC 50 / 4h	> 4.178 mg/l (rat) (OECD-403 (Aerosol))
2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine		
Oral	LD50	1030 mg/kg (rat)
Dermal	LD50	1840 mg/kg (rabbit)
69-72-7 Salicylic acid		
Oral	LD50	891 mg/kg (rat)
Dermal	LD 50	> 2000 mg/kg (rat)
64742-95-6 Hydrocarbons, C9, aromatics		
Oral	LD 50	> 3500 mg/kg (rat) (OECD 401)
Dermal	LD 50	> 3160 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 /4h	> 6193 mg/m ³ (rat) (OECD Guideline 403, vapour)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes severe skin burns and eye damage.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **Subacute to chronic toxicity:** No further relevant information available.
- **Sensitisation** Sensitisation possible through skin contact.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Carcinogenicity** No further relevant information available.
- **Reproductive toxicity/Fertility** No further relevant information available.
- **Reproductive toxicity/Teratogenicity** No further relevant information available.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

100-51-6 Benzyl alcohol

EL50/72h	700 mg/l (algae)
LC50/96h	10 mg/l (Lepomis macrochirus)

69-72-7 Salicylic acid

EC50	180 mg/l (daphnia) (24h)
EC50/48h	870 mg/l (daphnia magna) (OECD 202)
EC50/72h	100 mg/l (Pseudokirchneriella subcapitata)
	> 100 mg/l (desmodesmus subspicatus)
LC50/96h	1380 mg/l (pimephales promelas)

64742-95-6 Hydrocarbons, C9, aromatics

EC50/48h	7.4 mg/l (daphnia magna)
----------	--------------------------

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.11.2015

V - 1

Revision: 18.11.2015

Trade name: YACHTCARE EPOXY LIGHTFILLER (Hardener) *NEW*

(Contd. of page 8)

EL50/48h	3.2 mg/l (daphnia) (OECD Guideline 202, mobility)
EL50/72h	2.9 mg/l (Pseudokirchneriella subcapitata) (OECD Guideline 201)
LL50/96h	9.2 mg/l (oncorhynchus aguabonita) (OECD Guideline 203)
NOELR (aqua chron.)	2.144 mg/l (daphnia magna) (21d, calculated by a computer model)

· 12.2 Persistence and degradability

64742-95-6 Hydrocarbons, C9, aromatics

Biodegradation > 70 % (-) (OECD Guideline 301 F, 28d)

· 12.3 Bioaccumulative potential

100-51-6 Benzyl alcohol

log Kow 1.05 (-)

69-72-7 Salicylic acid

log Pow 2.21 (-)

· Behaviour in environmental systems:

· 12.4 Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste disposal key:

The waste codes given above are to be considered recommendations; because of regional and industrial sector specific features, application of different waste codes is possible.

· European waste catalogue

07 02 04* other organic solvents, washing liquids and mother liquors

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA

UN1759

· 14.2 UN proper shipping name

· ADR

1759 CORROSIVE SOLID, N.O.S.
(ISOPHORONEDIAMINE)

· IMDG, IATA

CORROSIVE SOLID, N.O.S. (ISOPHORONEDIAMINE)

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.11.2015

V - 1

Revision: 18.11.2015

Trade name: YACHTCARE EPOXY LIGHTFILLER (Hardener) *NEW*

(Contd. of page 9)

· 14.3 Transport hazard class(es)

· ADR, IMDG, IATA



· Class 8 Corrosive substances.
· Label 8

· 14.4 Packing group

· ADR, IMDG, IATA III

· 14.5 Environmental hazards: Not applicable.

· 14.6 Special precautions for user

Warning: Corrosive substances.

· Danger code (Kemler): 80

· EMS Number: F-A,S-B

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5 kg

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 g

Maximum net quantity per outer packaging: 1000 g

· Transport category 3

· Tunnel restriction code E

· IMDG

· Limited quantities (LQ) 5 kg

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 g

Maximum net quantity per outer packaging: 1000 g

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· National regulations:

· Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 20.11.2015

V - 1

Revision: 18.11.2015

Trade name: YACHTCARE EPOXY LIGHTFILLER (Hardener) *NEW*

(Contd. of page 10)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

· **Department issuing MSDS: Abteilung Labor**

· **Contact: Frau S. Schaller**

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Flam. Liq. 3: Flammable liquids, Hazard Category 3
- Acute Tox. 4: Acute toxicity, Hazard Category 4
- Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B
- Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
- Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
- Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
- Skin Sens. 1A: Sensitisation - Skin, Hazard Category 1A
- Skin Sens. 1B: Sensitisation - Skin, Hazard Category 1B
- STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
- STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
- Asp. Tox. 1: Aspiration hazard, Hazard Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3