## International GTA007 Thinners & Solvents



## PRODUCT DESCRIPTION

Thinners and equipment cleaner for alkyd and vinyl based products.

PRODUCT INFORMATION

GTA007 Colour **Specific Gravity** 0.86 **Volume Solids** 0% **Typical Shelf Life** 2 yrs VOC (As Supplied) 860 g/lt

DRYING/OVERCOATING INFORMATION

Drying

Overcoating **Substrate Temperature** 

5°C (41°F) 10°C (50°F) 23°C (73°F) 35°C (95°F)

Overcoated By Max Min Max

APPLICATION AND USE

Hints Ventilation and Humidity Control Ensure adequate ventilation during use.

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

TRANSPORTATION: Storage

International GTA007 should be kept in securely closed containers during transport and storage.

STORAGE:

Exposure to air and extremes of temperature should be avoided. For the full shelf life of International GTA007 to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F.

Keep out of direct sunlight.

Safety

DISPOSAL: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to

harden before disposal.

GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line. Always use gloves and goggles and keep skin protected with overalls. Users should ensure they have a copy of the

Material Safety Datasheet for this product and that they are familiar with all the safety directions before use.

**IMPORTANT NOTES** The technical information and suggestions for use and application presented herein are not intended to be exhaustive,

but they represent the best information available to use and are believed to be reliable. They should not, however, be construed as controlling suggestions and there is no warranty of performance of our materials either expressed or implied. We urge that users of our materials conduct confirmatory tests to determine final suitability for their specific end uses. Because this datasheet is subject to changes from time to time, it is the user's responsibility to check that

this sheet is current prior to using the product.