



## 2nm 135° stern light, single, horizontal mount, silver anodized, with 2,5m cable

## 301-005

This LED Navigation light comes in black and silver, with the best technology available and impressive robustness. It is easy to install. Below is a list of more great features. For more detailed information, please download technical files.

- For Boats and Yachts up to 50m (164 ft)
- High quality materials used for long life.
- Water and vibration proof.
- No EMC noise on your AIS/VHF.
- Multivoltage 12 to 24 Volt.
- Worldwide approvals.
- Including potted-in power cable for ultimate waterproofness.
- 5 year warranty.

Horizontally mounted with 2,5m cable

Specifications	
Number	301-005
Light Color	White
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="https://www.lopolight.com.under-Service-8.5upport">www.lopolight.com.under-Service-8.5upport</a>
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,precabled with 2.5 meter shielded marine grade cable,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ,
	PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	
Operating Voltage	screws, Epoxy, Polyurethane
	screws, Epoxy, Polyurethane 10-32VDC
EAN	screws, Epoxy, Polyurethane  10-32VDC  5704438012806
EAN IP rating	screws, Epoxy, Polyurethane  10-32VDC  5704438012806  IP68



Specifications	
Current consumption (mA @ 12VDC)	110
Stock status	Usually in stock
Lead time	1-2 weeks
Current consumption (mA @ 24VDC)	50
Vessel size	Under 12M,12-20M,20-50M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	0.63 Kg
Weight (Oz)	22.22 Oz