



2nm tri-color, horizontal mount, with 0.7m cable

201-005

2nm tri-color, hor mnt, 0.7m

Horizontally mounted on HDPE base with 0,75m cable

Specifications	
Number	201-005
Light Color	Red,Green,White
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light, precabled with 0.75 meter shielded marine grade cable, Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438007840
IP rating	IP68
Power draw (W)	2,9
UPC Code	879343007843
Connection	0.7m cable

Specifications	
Current consumption (mA @ 12VDC)	213
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	123
Vessel size	12-20M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	0.52 Kg
Weight (Oz)	18.34 Oz